

AKSELKOBLING, FENAFLEX

Serie FF

FF040G
KILREM SUPER HC 1382MM

- Opp til 4° vinkelforskyvning
- Opp til 8mm aksiall forskyvning
- Opp til 6mm parallellforskyvning



PRODUKTBESKRIVELSE

Fenaflex er myke, elastiske og smørefrie koblinger som tåler avvik og forskyvninger på alle plan, samt at det er meget enkle å montere. Koblingene har også utmerkede støtdempende egenskaper som minimerer vibrasjoner og svingninger.


TEKNISKE DATA

A

104


Størrelse

40



Speed rpm/min	F40	F50	F60	F70	F80	F90	F100	F110	F120	F140	F160	F180	F200	F220	F250
100	0.25	0.69	1.33	2.62	3.93	5.24	7.07	9.16	13.9	24.3	39.5	65.7	97.6	121.0	154.0
200	0.50	1.38	2.66	5.24	7.86	10.50	14.10	18.30	27.9	48.7	79.0	131.0	195.0	243.0	307.0
300	0.75	2.07	3.99	7.86	11.80	15.75	21.20	27.50	41.8	73.0	118.0	197.0	294.0	364.0	461.0
400	1.01	2.76	5.32	10.50	15.70	20.90	28.30	36.60	55.7	97.4	158.0	263.0	391.0	486.0	615.0
500	1.26	3.46	6.65	13.10	19.60	26.20	35.30	45.80	68.6	122.0	197.0	328.0	488.0	607.0	768.0
600	1.51	4.15	7.98	15.70	23.60	31.40	42.40	55.00	83.6	146.0	237.0	394.0	586.0	729.0	922.0
700	1.76	4.84	9.31	18.30	27.50	36.60	49.50	64.30	95.0	170.0	278.0	450.0	690.0	860.0	1078.0
720	1.81	4.98	9.57	18.80	28.30	37.70	50.80	66.00	100.0	175.0	284.0	473.0	703.0	875.0	1096.0
800	2.01	5.53	10.60	20.90	31.40	41.90	56.50	73.30	110.0	195.0	316.0	525.0	781.0	972.0	1229.0
900	2.21	6.07	11.60	23.00	34.50	45.90	62.40	79.70	120.0	210.0	340.0	560.0	830.0	1030.0	1280.0
1000	2.51	6.91	13.30	26.20	38.60	52.40	70.70	91.60	130.0	243.0	395.0	630.0	940.0	1170.0	1470.0
1200	3.02	8.29	16.00	31.40	47.00	62.80	84.80	110.00	160.0	290.0	470.0	760.0	1150.0	1420.0	1770.0
1400	3.52	9.69	18.60	36.60	55.00	72.90	99.00	130.00	190.0	341.0	550.0	890.0	1340.0	1650.0	2070.0
1440	3.62	9.95	19.10	37.70	56.50	75.40	102.00	132.00	201.0	351.0	568.0	910.0	1380.0	1700.0	2140.0
1600	4.02	11.10	21.30	41.90	62.80	83.60	113.00	147.00	220.0	380.0	620.0	1000.0	1500.0	1850.0	2320.0
1800	4.52	12.40	23.90	47.00	70.70	94.20	127.00	165.00	250.0	430.0	700.0	1150.0	1700.0	2100.0	2620.0
2000	5.03	13.80	26.60	52.40	78.60	105.00	141.00	185.00	279.0	480.0	780.0	1250.0	1900.0	2350.0	2940.0
2200	5.53	15.20	29.30	57.90	86.40	115.00	155.00	202.00	300.0	530.0	860.0	1350.0	2050.0	2500.0	3160.0
2400	6.03	16.60	31.90	62.80	94.20	125.00	170.00	220.00	330.0	580.0	940.0	1450.0	2200.0	2700.0	3380.0
2600	6.53	18.00	34.60	68.10	102.00	136.00	184.00	240.00	360.0	630.0	1020.0	1550.0	2350.0	2850.0	3600.0
2800	7.04	19.40	37.20	73.30	110.00	147.00	200.00	260.00	390.0	680.0	1100.0	1650.0	2500.0	3000.0	3820.0
2880	7.24	19.90	38.30	75.40	113.00	151.00	205.00	265.00	395.0	690.0	1110.0	1660.0	2510.0	3010.0	3830.0
3000	7.54	20.70	39.90	78.60	116.00	154.00	209.00	270.00	400.0	700.0	1120.0	1670.0	2520.0	3020.0	3840.0
3600	9.05	24.90	47.90	94.20	141.00	185.00	250.00	330.00	480.0	860.0	1380.0	2200.0	3300.0	4000.0	5000.0

The figures in heavier type are for standard motor speeds. All these power ratings are calculated at constant torque. For speeds below 100 rev/min and intermediate speeds use nominal torque ratings.



DIMENSIONS OF FENAFLEX FLANGES TYPES F & H

Category & Code	Size	Type	Shaft		Flange		Type F A1		Type B		Category & Code	A	C	Z	F	FA	M ₁	M ₂	Part No.
			Ø	h	Ø	h	Ø	h	Ø	h									
ISO1000	F40	B	25	10	25	10	25	10	25	10	25	30	22	14	6	-	112	0	0.00
ISO1000	F50	B	30	12	30	12	30	12	30	12	30	35	26	16	8	-	112	0	0.00
ISO1000	F60	B	35	14	35	14	35	14	35	14	35	40	30	20	10	-	112	0	0.00
ISO1000	F70	B	40	16	40	16	40	16	40	16	40	45	35	25	12	-	112	0	0.00
ISO1000	F80	B	45	18	45	18	45	18	45	18	45	50	40	30	15	-	112	0	0.00
ISO1000	F90	B	50	20	50	20	50	20	50	20	50	55	45	35	18	-	112	0	0.00
ISO1000	F100	B	55	22	55	22	55	22	55	22	55	60	50	40	20	-	112	0	0.00
ISO1000	F110	B	60	24	60	24	60	24	60	24	60	65	55	45	22	-	112	0	0.00
ISO1000	F120	B	65	26	65	26	65	26	65	26	65	70	60	50	25	-	112	0	0.00
ISO1000	F140	B	75	30	75	30	75	30	75	30	75	80	70	60	30	-	112	0	0.00
ISO1000	F160	B	85	34	85	34	85	34	85	34	85	90	80	70	35	-	112	0	0.00
ISO1000	F180	B	95	38	95	38	95	38	95	38	95	100	90	80	40	-	112	0	0.00
ISO1000	F200	B	105	42	105	42	105	42	105	42	105	110	100	90	45	-	112	0	0.00
ISO1000	F220	B	115	46	115	46	115	46	115	46	115	120	110	100	50	-	112	0	0.00
ISO1000	F250	B	125	50	125	50	125	50	125	50	125	130	120	110	55	-	112	0	0.00
ISO1000	F40	H	25	10	25	10	25	10	25	10	25	30	22	14	6	-	112	0	0.00
ISO1000	F50	H	30	12	30	12	30	12	30	12	30	35	26	16	8	-	112	0	0.00
ISO1000	F60	H	35	14	35	14	35	14	35	14	35	40	30	20	10	-	112	0	0.00
ISO1000	F70	H	40	16	40	16	40	16	40	16	40	45	35	25	12	-	112	0	0.00
ISO1000	F80	H	45	18	45	18	45	18	45	18	45	50	40	30	15	-	112	0	0.00
ISO1000	F90	H	50	20	50	20	50	20	50	20	50	55	45	35	18	-	112	0	0.00
ISO1000	F100	H	55	22	55	22	55	22	55	22	55	60	50	40	20	-	112	0	0.00
ISO1000	F110	H	60	24	60	24	60	24	60	24	60	65	55	45	22	-	112	0	0.00
ISO1000	F120	H	65	26	65	26	65	26	65	26	65	70	60	50	25	-	112	0	0.00
ISO1000	F140	H	75	30	75	30	75	30	75	30	75	80	70	60	30	-	112	0	0.00
ISO1000	F160	H	85	34	85	34	85	34	85	34	85	90	80	70	35	-	112	0	0.00
ISO1000	F180	H	95	38	95	38	95	38	95	38	95	100	90	80	40	-	112	0	0.00
ISO1000	F200	H	105	42	105	42	105	42	105	42	105	110	100	90	45	-	112	0	0.00
ISO1000	F220	H	115	46	115	46	115	46	115	46	115	120	110	100	50	-	112	0	0.00
ISO1000	F250	H	125	50	125	50	125	50	125	50	125	130	120	110	55	-	112	0	0.00
ISO1000	F40	B	25	10	25	10	25	10	25	10	25	30	22	14	6	-	112	0	0.00
ISO1000	F50	B	30	12	30	12	30	12	30	12	30	35	26	16	8	-	112	0	0.00
ISO1000	F60	B	35	14	35	14	35	14	35	14	35	40	30	20	10	-	112	0	0.00
ISO1000	F70	B	40	16	40	16	40	16	40	16	40	45	35	25	12	-	112	0	0.00
ISO1000	F80	B	45	18	45	18	45	18	45	18	45	50	40	30	15	-	112	0	0.00
ISO1000	F90	B	50	20	50	20	50	20	50	20	50	55	45	35	18	-	112	0	0.00
ISO1000	F100	B	55	22	55	22	55	22	55	22	55	60	50	40	20	-	112	0	0.00
ISO1000	F110	B	60	24	60	24	60	24	60	24	60	65	55	45	22	-	112	0	0.00
ISO1000	F120	B	65	26	65	26	65	26	65	26	65	70	60	50	25	-	112	0	0.00
ISO1000	F140	B	75	30	75	30	75	30	75	30	75	80	70	60	30	-	112	0	0.00
ISO1000	F160	B	85	34	85	34	85	34	85	34	85	90	80	70	35	-	112	0	0.00
ISO1000	F180	B	95	38	95	38	95	38	95	38	95	100	90	80	40	-	112	0	0.00
ISO1000	F200	B	105	42	105	42	105	42	105	42	105	110	100	90	45	-	112	0	0.00
ISO1000	F220	B	115	46	115	46	115	46	115	46	115	120	110	100	50	-	112	0	0.00
ISO1000	F250	B	125	50	125	50	125	50	125	50	125	130	120	110	55	-	112	0	0.00
ISO1000	F40	H	25	10	25	10	25	10	25	10	25	30	22	14	6	-	112	0	0.00
ISO1000	F50	H	30	12	30	12	30	12	30	12	30	35	26	16	8	-	112	0	0.00
ISO1000	F60	H	35	14	35	14	35	14	35	14	35	40	30	20	10	-	112	0	0.00
ISO1000	F70	H	40	16	40	16	40	16	40	16	40	45	35	25	12	-	112	0	0.00
ISO1000	F80	H	45	18	45	18	45	18	45	18	45	50	40	30	15	-	112	0	0.00
ISO1000	F90	H	50	20	50	20	50	20	50	20	50	55	45	35	18	-	112	0	0.00
ISO1000	F100	H	55	22	55	22	55	22	55	22	55	60	50	40	20	-	112	0	0.00
ISO1000	F110	H	60	24	60	24	60	24	60	24	60	65	55	45	22	-	112	0	0.00
ISO1000	F120	H	65	26	65	26	65	26	65	26	65	70	60	50	25	-	112	0	0.00
ISO1000	F140	H	75	30	75	30	75	30	75	30	75	80	70	60	30	-	112	0	0.00
ISO1000	F160	H	85	34	85	34	85	34	85	34	85	90	80	70	35	-	112	0	0.00
ISO1000	F180	H	95	38	95	38	95	38	95	38	95	100	90	80	40	-	112	0	0.00
ISO1000	F200	H	105	42	105	42	105	42	105	42	105	110	100	90	45	-	112	0	0.00
ISO1000	F220	H	115	46	115	46	115	46	115	46	115	120	110	100	50	-	112	0	0.00
ISO1000	F250	H	125	50	125	50	125	50	125	50	125	130	120	110	55	-	112	0	0.00

The figures in heavier type are for standard motor speeds. All these power ratings are calculated at constant torque. For speeds below 100 rev/min and intermediate speeds use nominal torque ratings.