

USK-M / USK-P

Rørkobling - Rett

5020.330.012

Rørkobling AIRflex USK-M M12x1,5



- vanntett og støv resistent
- Friksjons og vibrasjons tolerant
- IP 54
- -10 °C till +110 °C
- Passer til AirFlex-KUW-PVC-AS og PU-AS




**PRODUKTBESKRIVELSE**

| | |
|------------------|---------------------|
| Materiale | Polypropylen |
| Temperaturområde | -10 °C till +110 °C |
| Godkjenninger | |

Koblingsdel med sekskantetskiftenøkkeloverflate og tilkoblingstråd.

TEKNISKE DATA

| | |
|-----------------------|---------------------------------------|
| Diameter | 14 mm |
| Farge | Grå |
| Forpakkingsstørrelse | 50 pc |
| Gjenger | M12x1,5 met. EN 60423 |
| Godkjenninger | CSA 22.2, UL |
| IP-klasse | IP54 |
| Materiale | Polypropylen |
| Passer til | AIRFLEX KUW-PU-AS, AIRFLEX KUW-PVZ-AS |
| Temperaturområde fra | -10 °C |
| Temperaturområde til | 110 °C |
| Type | USK-M |
| Weight kg / 100 ± 10% | 0,66 |



USK-M


| IP54-65 | Ø | l mm | B mm | C mm | D mm |
|--------------|----|------|------|------|------|
| 5020.330.012 | 14 | 8,0 | 25,0 | 12,0 | 43,0 |
| 5020.330.016 | 17 | 11,0 | 30,0 | 12,0 | 43,0 |
| 5020.330.020 | 21 | 15,0 | 35,0 | 13,0 | 44,0 |
| 5020.330.025 | 27 | 20,0 | 44,0 | 13,0 | 50,0 |
| 5020.330.032 | 36 | 27,0 | 54,0 | 15,0 | 51,0 |
| 5020.330.040 | 45 | 35,0 | 63,0 | 15,0 | 51,0 |
| 5020.330.050 | 56 | 44,5 | 77,0 | 16,0 | 58,0 |
| 5020.330.063 | 56 | 44,5 | 77,0 | 16,0 | 58,0 |

USK-P

| IP54-65 | Ø | l mm | B mm | C mm | D mm |
|---------------|----|------|------|------|------|
| 5020.130.009* | 14 | 9,0 | 25,0 | 10,0 | 41,0 |
| 5020.130.011* | 17 | 11,0 | 30,0 | 10,0 | 41,0 |
| 5020.130.013 | 19 | 13,0 | 32,0 | 10,0 | 41,0 |
| 5020.130.016* | 21 | 14,5 | 35,0 | 11,0 | 42,0 |
| 5020.130.021 | 27 | 19,5 | 44,0 | 11,0 | 48,0 |
| 5020.130.029 | 36 | 27,0 | 54,0 | 12,0 | 48,0 |
| 5020.130.036 | 45 | 36,0 | 63,0 | 12,0 | 48,0 |
| 5020.130.048 | 56 | 46,0 | 77,0 | 15,0 | 57,0 |

USK-M

| IP54-65 | Ø | l mm | B mm | C mm | D mm |
|--------------|----|------|------|------|------|
| 5020.330.012 | 14 | 8,0 | 25,0 | 12,0 | 43,0 |
| 5020.330.016 | 17 | 11,0 | 30,0 | 12,0 | 43,0 |
| 5020.330.020 | 21 | 15,0 | 35,0 | 13,0 | 44,0 |
| 5020.330.025 | 27 | 20,0 | 44,0 | 13,0 | 50,0 |
| 5020.330.032 | 36 | 27,0 | 54,0 | 15,0 | 51,0 |
| 5020.330.040 | 45 | 35,0 | 63,0 | 15,0 | 51,0 |
| 5020.330.050 | 56 | 44,5 | 77,0 | 16,0 | 58,0 |
| 5020.330.063 | 56 | 44,5 | 77,0 | 16,0 | 58,0 |



USK-P

| IP54-65 | Ø | l mm | B mm | C mm | D mm |
|---------------|----|------|------|------|------|
| 5020.130.009* | 14 | 9,0 | 25,0 | 10,0 | 41,0 |
| 5020.130.011* | 17 | 11,0 | 30,0 | 10,0 | 41,0 |
| 5020.130.013 | 19 | 13,0 | 32,0 | 10,0 | 41,0 |
| 5020.130.016* | 21 | 14,5 | 35,0 | 11,0 | 42,0 |
| 5020.130.021 | 27 | 19,5 | 44,0 | 11,0 | 48,0 |
| 5020.130.029 | 36 | 27,0 | 54,0 | 12,0 | 48,0 |
| 5020.130.036 | 45 | 36,0 | 63,0 | 12,0 | 48,0 |
| 5020.130.048 | 56 | 46,0 | 77,0 | 15,0 | 57,0 |