

## BELGVENTIL I RUSTFRITT STÅL

Avstengningsventil med metallbelg

### MBSOV-SERIEN

Avstengningsventil med metallbelg

- Trykk: PN 40
- Cv: 1,4
- Temperaturområde: -20 til 70 °C
- Vekt: 0,4 kg



D42528



D43129

## PRODUKTBESKRIVELSE

### Applikasjoner

- Rene gassapplikasjoner
- Høyflow-systemer
- Renseprosesser
- Brukes i hovedlinjer

### Fordeler


- Helmetallisk design som forhindrer gassforurensning
- Belg og ventilsete i rustfritt stål
- Fargekodet gass på håndhullet for enkel identifikasjon
- Rengjort for oksygenapplikasjoner
- Fri for olje og fett

Example for selecting a part number:


| D43129           | AR  | 11  |
|------------------|---|---|
| BASIC SERIES     | GAS TYPE LABELING ON HANDKNOB AND CAPS  | CONNECTIONS   |
| D42528<br>D43129 | According to DIN EN 13792*<br>AR = Chrome and silver series<br>*Color, handle and cap + gas label according to DIN EN 13792<br>*State type of gas when ordering. Standard color for handle and cap. Please ask for additional colors if needed. | 00 - Female G 1/8<br><br>*Compression fittings in Brass/Stainless Steel are available, please refer to disclaimer "Fittings". |

Note: When selecting valves, the compatibility of the materials with the process gas must be verified.

D42528



D43129




Example for selecting a part number:

| D43129           | AR  | 11  |
|------------------|---|---|
| BASIC SERIES     | GAS TYPE LABELING ON HANDKNOB AND CAPS  | CONNECTIONS   |
| D42528<br>D43129 | According to DIN EN 13792*<br>AR = Chrome and silver series<br>*Color, handle and cap + gas label according to DIN EN 13792<br>*State type of gas when ordering. Standard color for handle and cap. Please ask for additional colors if needed. | 00 - Female G 1/8<br><br>*Compression fittings in Brass/Stainless Steel are available, please refer to disclaimer "Fittings". |

Note: When selecting valves, the compatibility of the materials with the process gas must be verified.

D42528



D43129

