

## 4 POLT C9 RELE

Serie QRC

C9A4124A

Miniatyrrele QRC 4-pol 5A 24V AC (EL4378502)

- 5 A
- Fargekodet testknapp
- Merkesystem
- Mekanisk indikering



### PRODUKTBESKRIVELSE

### TEKNISKE DATA

#### INNGANGSDATA

|                           |         |
|---------------------------|---------|
| Arbeidsområde Un          | 0,8-1,1 |
| Spoleffekt                | 1,2     |
| Spolespenning AC          | 24      |
| Fraslagsspenning Un maks. | 0,25    |

#### UTGANGSDATA

|                              |                              |
|------------------------------|------------------------------|
| Antall kontakter             | 4                            |
| Kontaktalternativer          | Standard                     |
| Kontaktmateriale             | AgNi + 0,2 µ Au              |
| Brytevne spenning            | 250                          |
| Brytevne strøm               | 5 A                          |
| Anbefalt last maks.          | 5 A/250V AC-1; 5 A/30 V DC-1 |
| Anbefalt last min.           | 10 mA/10 V                   |
| Resistiv last 110 V DC maks. | 50                           |
| Resistiv last 24 V DC maks.  | 100                          |
| Mekanisk levetid             | AC: 10 Mill./DC: 20 Mill     |
| Støtstrøm (20ms)             | 15 A                         |
| Fraslagstid                  | 6                            |

## GENERELL DATA

|                            |                                         |
|----------------------------|-----------------------------------------|
| IP-klasse                  | IP40                                    |
| Isolasjon kontakt/kontakt  | 2500                                    |
| Isolasjon kontakt/spole    | 2000                                    |
| Temperaturområde fra       | -40 °C                                  |
| Oppbevaringstemperatur fra | -40 °C                                  |
| Oppbevaringstemperatur til | 80 °C                                   |
| Temperaturområde til       | 60 °C                                   |
| Frekvens                   | 50                                      |
| Vekt                       | 43                                      |
| Godkjenninger              | CE, Gost R, RoHS, CCC, CSA, Lloyd's, UL |



