

VM-3

3 ventils manifold

VM-3

- Komplet SS316
- Maks. 420 bar
- PTFE eller grafitt pakning



PRODUKTBESKRIVELSE

3-veis manifold brukes hvor en relativ transmitter er installert. Manifolden kommer i SS316 med PTFE pakning, som opsjon kan den skaffes med grafitt pakning. For temperaturgraf vennligst se datablad.

Opsjon

- Grafitt pakning
- Oksygenvasket

TEKNISKE DATA

Materiale	SS316
Materiale medieberørte deler	Grafitt, PTFE
Tilkobling	1/2" NPT
Trykkområde maks.	420 bar
Vekt	1,8 kg

Ordering procedure		Code	Product
Valve manifold:	3-valve - VM-3	A	Set of M10 covers for fitting the transmitter
	5-valve - VM-5	B	Set of 7/16" x 25 mm screws for fitting the transmitter
		C	Set of 7/16" x 55 mm screws for fitting the transmitter with covers
Special versions:		1	Set of weldable stainless steel connectors (316ss)
R1 - conventional versions (only VM-3)		2	Set of weldable steel connectors (A11552)
R2 - conventional versions		3	Set of connectors with O12 clamping ring
Graphite - graphite gpm packing		4	Set of connectors with O14 clamping ring
Titan - valve adapted to contact with oxygen	Additional equipment	U	Handle for mounting the valve

Ordering procedure		Code	Product
Valve manifold:	3-valve - VM-3	A	Set of M10 covers for fitting the transmitter
	5-valve - VM-5	B	Set of 7/16" x 25 mm screws for fitting the transmitter
		C	Set of 7/16" x 55 mm screws for fitting the transmitter with covers
Special versions:		1	Set of weldable stainless steel connectors (316ss)
R1 - conventional versions (only VM-3)		2	Set of weldable steel connectors (A11552)
R2 - conventional versions		3	Set of connectors with O12 clamping ring
Graphite - graphite gpm packing		4	Set of connectors with O14 clamping ring
Titan - valve adapted to contact with oxygen	Additional equipment	U	Handle for mounting the valve