

KABELJENNOMFØRING

KES, KES-R, KES-GB

28652.4

KES-R 16/24, Kabelgjennomføring med klikkfeste, svart

- For kabeldiametre fra 3,2 mm til 20,5 mm
- Dobbel tetning til IP66
- Ecolab-godkjent
- Polyamid 6.6 glassfiberforsterket kjerne
- Integrert strekkavlastning i henhold til EN62444



PRODUKTBESKRIVELSE

TEKNISKE DATA

GENERELL INFO

Type	KES-R
Montering	Clip on
Farge	Svart
IP-klasse	IP66
NEMA class	4x
Number of cables	16
Number of cables x cable diameter	6 x 5.0mm-8.5mm, 8 x 3.2mm-5.5mm, 2 x 9.5mm-14.5mm
Lengde	149,6
Bredde	58
Installed height	14,5

MONTERINGSINFORMASJON

Wall thickness	1.5mm-2.0mm
Length of cutout	112
Width of cutout	36

MATERIALE

Materiale	Polyamid 6.6
Glass-fibre reinforced	Ja
Flammeklasse	V-0
Sealing material	TPE
Silicone-free	Ja
Halogenfri	Ja
Temperaturområde drift fra	-40 °C
Temperaturområde drift til	90 °C

GODKJENNINGER

UL test standard	UL 508A
cUL test standard	C22.2 No. 14-18

ØVRIG DATA

Tariff code	39259020
Country of origin	DE
Vekt	113,3
Forpakningsstørrelse	10



You can choose one of three attachment options to fit your requirements

1. Screw-on mount



The KES (without threaded bush) is screwed from the outside onto the housing wall.

2. Screw-on mount with threaded bushes and latching clips



Using the latching clips, the KES-GB latches onto the outside of the housing wall. It is then screwed on from the inside, through the housing wall, using the integrated threaded bushes.


3. Latched (snap-on) mount using latching hooks



The KES-R is latched from outside to the housing wall using the latching clips.

KES 16/24

8x Ø3.2 - 5.5mm
6x Ø5.0 - 8.5mm
2x Ø9.5 - 11.5mm



Panel cut-out
for wall thickness
1.5 – 2 mm
(for snap-on attachment)



You can choose one of three attachment options to fit your requirements

1. Screw-on mount



The KES (without threaded bush) is screwed from the outside onto the housing wall.

2. Screw-on mount with threaded bushes and latching clips



Using the latching clips, the KES-GB latches onto the outside of the housing wall. It is then screwed on from the inside, through the housing wall, using the integrated threaded bushes.

3. Latched (snap-on) mount using latching hooks



The KES-R is latched from outside to the housing wall using the latching clips.

