

## ECH-SERIE

ECH40-10  
ECH40-10

- Mulig med kundetilpassning
- IP40 // IP65
- Ta kontakt for din variant



### PRODUKTBESKRIVELSE

ECH-serien er enkle lineære solenoider hvor slagbevegelsen utføres fra begynnelse til sluttposisjon av de elektromagnetiske kreftene. Retur til startposisjonen er skjer ved hjelp av ytre krefter, eller av en fjær som er bygd inn i magnetventilen.

### TEKNISKE DATA

Absorbed power @ 20°C, 100% duty	13
Absorbed power @ 20°C, 15% duty	75
Absorbed power @ 20°C, 25% duty	45
Absorbed power @ 20°C, 40% duty	30
Absorbed power @ 20°C, 5% duty	210
Beginning of stroke force at 100% duty	9,5
Beginning of stroke force at 15% duty	30
Beginning of stroke force at 25% duty	23
Beginning of stroke force at 40% duty	18
Beginning of stroke force at 5% duty	50
End of stroke force at 100% duty	10,4
End of stroke force at 15% duty	27
End of stroke force at 25% duty	19,5
End of stroke force at 40% duty	16
End of stroke force at 5% duty	43
IP class of solenoid body and connector	IP40
IP class of solenoid mounting face	IP65

