



SIRENE SERIE H

712100113

HPT Horn 108dB 240V AC (EL6201716)

- Membransirene
- 108 dB
- IP67 HTGL



PRODUKTBESKRIVELSE

Kraftig horn for ute og innebruk. Kan for eks. brukes i industri og havneanlegg. Finnes med inngang for telefonsignal på forespørsel (HPTR).

TEKNISKE DATA

Antall toner	1 pc
Farge hus	Grå RAL 7035
IP-klasse	IP55
Koblingsklemme	2,5 mm ²
Lydnivå maks.	108 dB
Lydnivå min.	108 dB
Matespenning	230 V AC
Matespenning AC maks.	253 V AC
Matespenning AC min.	207 V AC
Montering	Vertikal
Nominell strøm maks.	0,1 A
Nominell strøm min.	0,1 A
Temperaturområde fra	-20 °C
Temperaturområde til	50 °C

Tonfrekvens maks.	50 Hz
Tonfrekvens min.	50 Hz
Vekt	800 g

The sound pressure decreases by 6 dB when doubling the distance; the following distance table is to be seen as indication, as also factors like tone type, wind speed, wind direction, humidity, weather conditions etc. do influence the sound pressure level.

Distance (m)	Sound pressure dB (A)																				
1	65	70	75	80	85	90	92	94	96	98	100	102	104	106	108	110	112	114	116	118	120
2	59	64	69	74	79	84	86	88	90	92	94	96	98	100	102	104	106	108	110	112	114
3	55	60	65	70	75	80	82	84	86	88	90	92	94	96	98	100	102	104	106	108	110
5	51	56	61	66	71	76	78	80	82	84	86	88	90	92	94	96	98	100	102	104	106
10	45	50	55	60	65	70	72	74	76	78	80	82	84	86	88	90	92	94	96	98	100
20	39	44	49	54	59	64	66	68	70	72	74	76	78	80	82	84	86	88	90	92	94
30	35	40	45	50	55	60	62	64	66	68	70	72	74	76	78	80	82	84	86	88	90
50		36	41	46	51	56	58	60	62	64	66	68	70	72	74	76	78	80	82	84	86
100			40	45	50	52	54	56	58	60	62	64	66	68	70	72	74	76	78	80	
200			39	44	48	50	52	54	56	58	60	62	64	66	68	70	72	74			
500				38	40	42	44	46	48	50	52	54	56	58	60	62	64	66			

The sound pressure decreases by 6 dB when doubling the distance

