


SL 811 PUR motor connection cable with PVC cores 0.6/1 kV

BRÖCKSKES · D-VIERSEN · SL 811 0,6/1 kV 4 x 1,5 mm² CE



Marking for SL 811 08110415:

SAB BRÖCKSKES · D-VIERSEN · SL 811 0,6/1 kV 4 x 1,5 mm² CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, EN 60228, VDE 0295, class 6
Insulation:	PVC, TI2 acc. to DIN VDE 0281 part 1 + HD 21.1
Colour code:	black cores with consecutive numbers acc. to EN 50334 and a green-yellow earth wire
Stranding:	in layers
Wrapping:	non-woven tape
Sheath material:	PUR, TMPU acc. to DIN VDE 0282 part 10 + HD 22.10 with mat surface
Sheath colour:	grey (RAL 7000)

Outstanding features:

- flexible
- rugged sheath
- oil resistant
- EAC approval

Technical data:

Nominal voltage:	U ₀ /U 0.6/1 kV
Testing voltage U:	4000 V
Min. bending radius	
<i>fixed laying:</i>	4 x d
<i>flexible application:</i>	6 x d
<i>continuously flexible:</i>	10 x d
Radiation resistance:	5 x 10 ⁷ cJ/kg
Temperature range	
<i>fixed laying:</i>	-40/+70 °C
<i>flexible application:</i>	+5/+70 °C
Oil resistance:	very good - PUR TMPU acc. to DIN VDE 0282 part 10 + HD 22.10
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Absence of harmful substances:	acc. to RoHS directive of the European Union see page N/17

item no.	no. of cores x cross section n x mm ²	AWG	largest single wire ø mm	outer-ø ± 5 % mm	copper figure kg/km	cable weight ≈ kg/km
08110415	4 x 1,50	16 / 4c	0,16	9,3	57,6	125
08110425	4 x 2,50	14 / 4c	0,16	11,1	96,0	191
08110440	4 x 4,00	12 / 4c	0,16	12,9	153,6	268
08110460	4 x 6,00	10 / 4c	0,21	14,7	230,4	356
08110470	4 x 10,00	8 / 4c	0,21	18,5	384,0	601
08110480	4 x 16,00	6 / 4c	0,21	21,9	614,4	862
08110490	4 x 25,00	4 / 4c	0,21	26,2	960,0	1297
08110495	4 x 35,00	2 / 4c	0,21	29,5	1344,0	1751
08110496	4 x 50,00	1 / 4c	0,31	35,0	1920,0	2423
08110515	5 x 1,50	16 / 5c	0,16	10,6	72,0	154
08110525	5 x 2,50	14 / 5c	0,16	12,8	120,0	230
08110540	5 x 4,00	12 / 5c	0,16	14,2	192,0	317
08110560	5 x 6,00	10 / 5c	0,21	16,7	288,0	449
08110570	5 x 10,00	8 / 5c	0,21	20,4	480,0	739
08110580	5 x 16,00	6 / 5c	0,21	24,6	768,0	1079
08110590	5 x 25,00	4 / 5c	0,21	28,9	1200,0	1597

Other dimensions and colours are possible on request.